



# Profile® Wood Hydraulic Mulch



GREEN DESIGN ENGINEERING™  
EARTH-FRIENDLY SOLUTIONS  
FOR SUSTAINABLE RESULTS™

Solutions for your Environment™

## Description

Profile® Wood is a biodegradable, Hydraulic Mulch (HM) composed of 100% recycled Thermally Refined™ virgin wood fibers derived from whole wood chips. The HM is made in the US, plastic-free, and phytosanitized to eliminate potential weed seeds and pathogens. Upon application, the product forms an intimate bond with the soil surface to create a porous, absorbent and flexible erosion resistant blanket that allows for rapid germination and accelerated plant growth.

## Recommended Applications

- Erosion control and revegetation for moderate slopes (≤2H:1V)
- Rough graded slopes
- Enhancement of vegetation establishment

## Technical Data

Physical Properties*	Test Method	Units	Tested Value
Specification for Hydraulically-Applied Wood Fiber Mulch	ASTM D8198-Type1	Compliant	Yes
Mass/Unit Area	ASTM D6566 <sup>1</sup>	g/m <sup>2</sup> (oz/yd <sup>2</sup> )	≥ 336 (9.9)
Water Holding Capacity	ASTM D7367	%	≥ 1,200
Material Color	Observed	n/a	Green
Performance Properties*	Test Method	Units	Tested Value
Cover Factor <sup>2</sup>	ASTM D8298-Type 1	n/a	≤ 0.30
Percent Effectiveness <sup>3</sup>	ASTM D8298-Type 1	%	≥ 70
Vegetation Establishment	ASTM D7322	%	≥ 200
Functional Longevity <sup>4</sup>	ASTM D5338	months	≤ 3
Environmental Properties*	Test Method	Units	Tested Value
Ecotoxicity <sup>5</sup>	EPA 2021.0	n/a	Non-Toxic
Biodegradability	ASTM D5338	n/a	Yes
USDA BioPreferred® Biobased Content	ASTM D6866	%	99
Elemental Impurity Limits	ASTM D8082	Pass/Fail	Pass
Product Composition			Typical Value
Thermally Processed Wood Fibers <sup>6</sup> (within a pressurized vessel)			100%

\* When uniformly applied at a rate of 3,000 pounds per acre (3,400 kilograms/hectare) under laboratory conditions. 1. ASTM test methods developed for Rolled Erosion Control Products that have been modified to accommodate Hydraulic Erosion Control Products. 2. Cover Factor is calculated as soil loss ratio of treated surface versus an untreated control surface. 3. % Effectiveness = One minus Cover Factor multiplied by 100%. 4. Functional Longevity is the estimated time period, based upon field observations, that a material can be anticipated to provide erosion control and agronomic benefits as influenced by composition, as well as site-specific conditions, including; but not limited to – temperature, moisture, light conditions, soils, biological activity, vegetative establishment and other environmental factors. 5. 48-hour LC<sub>50</sub> > 100% - LC<sub>50</sub> refers to the percent concentration of a substance in water when 50% percent mortality of an organism is reached. 50% mortality of the tested species (*Daphnia magna*) could not be achieved when subjected to 100% effluent concentration proving the material to be acutely non-toxic. 6. Heated to a temperature greater than 380 degrees Fahrenheit (193 degrees Celsius) for 5 minutes at a pressure greater than 50 psi (345 kPa) in order to be Thermally Refined™/Processed and to achieve phytosanitation.



## Made in USA Packaging Data

Properties	Test Method	Units	Nominal Value
Bag Weight	Scale	kg (lb)	22.7 (50)
Bags per Pallet	Observed	#	40

UV and weather-resistant plastic bags. Pallets are weather-proof stretch wrapped with UV resistant pallet cover.

## Profile Products

750 Lake Cook Road, Ste. 440  
Buffalo Grove, IL 60089  
800-508-8681 or +1-847-215-3464  
[www.profileproducts.com](http://www.profileproducts.com)

To the best of our knowledge, the information contained herein is accurate. However, Profile Products cannot assume any liability whatsoever for the accuracy or completeness thereof. Final determination of the suitability of any information or material for the use contemplated, of its manner of use and whether the suggested use infringes any patents is the sole responsibility of the user.  
Profile Products 2021©